

Yamaha's Unique & Proven Solutions

IoT/M2M Integration system

Simplified Programming

Real-time Production Analysis

Flexible M2M communication

Smart Setup operations

Traceability

Remote Support



Smart Setup Operations

Component Setup Verification

Components setup verification function prevents invalid setup conditions.

Shows the setup / changeover on a guide display, and collates to verify that setting status is correct.



Rank Monitoring (YSUP-ST / YSUP-MI)

Bin code management for LED ranking can confirm the correct LED rank is being mounted.

Offline Setup Navigation (YSUP-ST)

Utilizes an off-line loading station and feeder cart to load components on feeders and

setup feeders on dedicated carts. All setups will be validated based on machine specific program setup conditions.



Material Time Limit Management (YSUP-ST / YSUP-MI)


Define and monitor setup and production times for any MSL ranked consumable. The system will reject those consumables that exceed defined time limits.



Real-time Production Analysis

Live Production Dashboard

Visualizes equipment operation, production OEE and quality conditions for the production floor or for each line. Customizable thresholds can be set for any parameter allowing for easy understanding of a failing condition. In addition, the dashboard display can be customized.





Production Analytics Dashboard

Production Analytics Dashboard utilizes business intelligence algorithms to convey a top-down approach to analyze cause and remedy solutions to improve production OEE.





Traceability Package

Production History Search (T-TOOL)

T-Tool captures real-time data related to PCB assembly and machine driven events. Users will be able to query serialized data to pinpoint information at component level; gaining more visibility to extensive relational data.



Accumulation of All Images (All Image Tracer)

Saves all of your mounter components recognition images on time, and all the way through the production process yet with no stress. Gives powerful support for analyzing component mounting quality.





Flexible M2M



APCO automates change over for tooling, programs, setup and conveyor width.




SEMI SMT-ELS M2M protocol is also available.

- SEMI SMT-ELS M2M is a communication standard between different machine manufacturers
 SEMI SMT-ELS details: https://global.yamaha-motor.com/business/smt/software/semi_smt-els/

Printer ← SPI Feedback


Defect result offsets from SPI can be fed back to printer to automatically adjust print offset. Also SPI machine can request stencil cleaning operation at printer.





Mounter <-> AOI Linking (QA Option)

AOI defect results can be fed back to the mounting process to provide equipment operator information related to the defect. In turn, allowing the opportunity to resolve the issue in real-time.




Mobile Decision Function

Communicates the inspection pass-fail results to an operator's mobile terminal.

Supports operator's efficient production by making the secondary judgement on the inspector results during machine operation.

Remote Support: Maintenance Package






Simplified Programing & Scheduling Package

Create PCB data from various CAD data formats easily. PCB programs are transferable between Yamaha equipment (Printer, SPI, Mounter, AOI)



Optimization via Automated Decision-Making (YSUP-PG)

Optimizes component setup positions and mounting sequences to realize efficient production. It is also possible to plan optimal setup groups or production sequences by considering the PCB surface, reflow conditions, soldering type, and other detailed conditions based on multiple PCB data.



Graphical User Interface

Real-time Drawing

Reflects changes made to a graphic immediately to create error-free component data.



3D Graphics

Displays the PCB data in a 3D image to make it easier to see the mounting status of components.



Mounting Simulation


Displays a virtual PCB based on the PCB design data* to check the PCB data for errors before actual mounting.

* PCB design data: Gerber data, ODB++, etc.



Multi-monitor Support

Displays two screens simultaneously to realize comfortable operability.



Yamaha Motor Europe N.V. Niederlassung Deutschland, Geschäftsbereich Robotik German Branch Office, Robotics Business Hansemannstrasse 12 · 41468 Neuss · Germany Tel: +49-2131-2013520 ymerobotics.info@yamaha-motor.de www.yamaha-motor-robotics.eu

The models shown in the photographs in this catalog may differ slightly from the standard specifications. Specifications and appearance are subject to change without prior notice.

Yamaha Motor Co. Ltd., Head office Robotics Operation 127 Toyooka, Kita-ku, Hamamatsu, Shizuoka 433-8103, Japan, Tel.: 81-53-525-7061

Yamaha Motor IM (Suzhou) Co. Ltd. #8 Building No.17 East Suhong Road, Suzhou Industrial Park, China 215026, Tel.: 86-512-6831-7091 Yamaha Motor IM (Suzhou) Co. Ltd., Shenzhen Branch, 1/F, Bd. 1, Yesun Intelligent Community, Guanguang Rd. 1301-70, Guanlan St, Longhua District Shenzhen, Guangdong, P.R.C. China, Tel.: 86-755-2393-9910 Yamaha Motor Corporation, U.S.A., IM Division (USA office) 3065 Chastain Meadows Parkway Marietta, GA 30066, Tel.: 1-770-420-5825

Thai Yamaha Motor Co. Ltd. (Thailand Office), 64 Moo1, Debaratana Rd., Km 21, Tambol Srisa Jorrake Yai, Amphur Bangsaothong, Samutprakarn 10570, Thailand, Tel.: 66-96-779-7680 Yamaha Motor Parts Manufacturing Vietnam Co. Ltd. (Vietnam Office)

Lot G1-G2, Thang Long Industrial Park, Vong La Com, Dong Anh Dist, Hanoi, Vietnam, Tel.: 84-24-3951-6456